

General

Corded Scanner



Comfortable and Powerful

Delivering Outstanding Service and Value

Wherever handheld scanners are used, whether it's on the shop floor, at the checkout counter, in the manufacturing line, or in the documentation center, they must be comfortable and safe for the users and deliver undeniably accurate scans all day long. More importantly, they should be cost-effective to operate.

CipherLab designs and manufactures the industry's top handheld scanners to provide outstanding reliable service for workers and deliver a high return on investment (ROI). Reliability, user comfort, and power consumption 50% lower than competitor's devices on average make CipherLab scanners the ideal choice for long-lasting value in any industry.

1070

Designed to provide an affordable and reliable solution for overwhelming scanning demands on shop floors and at checkout stands, the CipherLab 1070 CCD scanner helps businesses streamline workflow and boost work productivity with consistent, accurate data capture. Its aesthetically designed lightweight form factor fits in nicely with any retail setting — even high-end boutiques. The ergonomic handle grip offers all-day comfort for intensive scanning tasks. Together with 3-year warranty, the 1070 ensures not only reliable capture of data and long-lasting performance, but also a significantly lowered total cost of ownership — offering a high return on investment for any retail business.



When it comes to reading a variety of symbologies and printed materials, CipherLab gives you the 1000 and 1090+. These CCD scanners not only deliver consistently accurate data capture in any retail environment, they also eliminate misreading clustered or poorly printed barcodes. Both are ideal for close scanning of wide barcodes with the 1090+ scanning up to 9mm and the 1000 reading high resolution barcodes up to 3mil. Both contact scanners come with smart ergonomic design enhanced with a thermoplastic polyurethane (TPU) rubber boot to give users a comfortable grip and long-lasting durability. Their imager build with no moving parts together with lower power consumption and a five-year warranty make them the perfect choice for reliable performance.



1100 1105

For manufacturing companies looking for scanners which are powerful, versatile and rugged, the CipherLab 1100 and 1105 linear imaging scanners would be the choice to go. Designed to endure the harsh working environment of manufactory factories, these CCD scanners carry no moving parts and are built with rugged double-injection molded TPU. They are also test-proven to withstand multiple 2 m (6.5 ft.) drops onto concrete and backed by CipherLab's five-year warranty to ensure long-lasting and reliable service. Aside the rugged build, both the 1100 and 1105 offer accurate data capture of multiple symbologies – with the 1100 to read high density barcodes as small as 3mil, which makes it ideal for tracking smaller parts and components marked by tiny labels.



1200

Ideal for manufacturing applications, the CipherLab 1200 laser scanner quickly and accurately reads barcodes up to 64 cm (12ft.) away – allowing you to work smarter and faster. Small size, ergonomic design, and light weight make the 1200 scanner easy and comfortable to use all day long.





| Performance | 0.1 | | | | | |
|-----------------------|--|--|---|--|--|--|
| | Category | CCD contact scanner | CCD contact scanner | CCD contact scanner (for codes up to 90mm wide) | Linear imaging scanner | Laser Scanner |
| | Optical sensor | 1500 pixels | 2048 pixels | | 3648 pixels | Laser |
| | Light source | Red LED (623 nm) | Red LED (660 nm) | Red LED (650 nm) | Red LED (630 nm) | Visible laser diode(650±15 nm) |
| | Resolution | 4 mil | 3 mil | 4 mil | 3 mil | 4 mil |
| | Depth of field 13 mil barcode | 0 to 3cm / 0 to 1.2 in. | 0 to 1cm / 0 to 0.4 in. | 0 to 5cm / 0 to 2 in. | 2.5 to 20 cm / 1 to 7.9 in. | 1 to 63 cm / 0.4 to 25 in. |
| | Scanning angle | Pitch ±70° | 2 Skew ±40° Pitch ±70° Skew ±70° | | Pitch ±70° Skew ±32.5° | |
| | PCS | Minimum 45% | Minimum 30% | | | |
| | Scan rate | | 100 scans / second | | | 35 ± 5 scans / second |
| | Auto-sense mode | | n/a Yes | | | n/a |
| | Interfaces supported | Keyboard wedge,USB | B RS232, Keyboard wedge, Wand emulation (except 1000), USB HID, USB Virtual Com, IBM 4683/4694 | | | |
| | Barcodes supported | | abar, Code 39, Code 93, Code 128, GS1 DataBar (RSS), Industrial 2 of 5, Interleave 2 of 5, MsI, Parmacodes, Plessey, Telepen, UPC / EAN / GS1-128, and more | | | |
| | Programmable features | | Data editing, interface selection, symbology configuration | | | |
| | Language support | US and | S and UK English, French, Italian, Belgian, Norwegian, Swedish, Spanish, Portuguese, German | | | |
| Physical | Dimension L x W x H | 16.7 x 7.5 x 5.7 cm / 6.6 x 3 x 2.2 in. | 17 x 8 x 4.8 cm / 6.7 x 3.1 x 1.9 in. | 18.2 x 10.4 x 6.4 cm / 7.2 x 4.1 x 2.5 in. | 14.5 x 9.3 x 7.4 cm / 5.7 x 3.7 x 2.9 in. | 14.5 x 9.3 x 7.4 cm / 5.7 x 3.7 x 2.9 in. |
| | Weight without cable | 104 g / 3.7 oz. | 265 g / 9.3 oz. (w/cable) | 148 g / 5.2 oz. | 165 g / 5.8 oz. | 190 g / 6.7 oz. |
| | Color | Black | Ivory or Black | lvory | Light gray or dark grey | |
| | Switch | Rubber switch | | | Micro switch | |
| Electrical | Voltage | +5V ±5% | | | +5V ±10% | +5V ±5% |
| | Power consumption Standby / Operating | 35 mA / 180 mA | 40 mA / 95 mA | 45 mA / 105 mA | 60 mA / 190 mA | 40 mA / 175 mA |
| User Environment — | Operating temperature | 0 ° to 50°C / 32° to 122°F | | | 0 ° to 40°C / 32° to 104°F | |
| | Storge temperature | -20° to 60°C / -4° to 140°F | | | -40° to 60°C / -40° to 140°F | |
| | Operating/storage humidity Non-condensing | 10% to 90% / 0% to 95% | 10% to 90% / 5% to 95% | | | |
| | Impact resistance Multiple drops onto concrete | 1.2 m / 4 ft. Drops | 1.0 m / 3.3 ft. Drops | | 2m / 6.6 ft. Drops | 1.2m / 4 ft. Drops |
| | Electrostatic discharge | | Conforms to ± 15 kV air discharge and ± 8 kV contact discharge | | | |
| | EMC regulation | BSMI, CCC, CE, C-Tick, FCC, IC, KCC | C BSMI, CE, C-Tick, FCC, IC, KCC | | BSMI, CE, C-Tick, FCC, IC | BSMI, CE, C-Tick, FCC, IC, KCC |
| Configuration | | Setup options include Windows®-based ScanMaster software (included), by direct connection or printing out barcode settings | | | | |
| Accessories | | | | e, desk / wall mount included with 1100 / 1200 tional auto-sense stand for 1100 | | |
| Warranty | | 3 years | 5 years 1 year | | | |

ACCESSORIES

Auto-sense Stand



1100/1105 & 1200 Holder Can be used on tabletop or wall mounted







HEADQUARTERS CipherLab Co., Ltd. 12F, 333 Dunhua S. Rd., Sec.2 Taipei, Taiwan 10669 Tel +886 2 8647 1166 Fax +886 2 8732 3300 www.cipherlab.com

CipherLab China CipnerLab China J Room, 4F, No.728 West Yan'an Road, Changning District, Shanghai China 200050 Tel +86 21 3368 0288 Fax +86 21 3368 0286

CipherLab USA 2552 Summit Avenue Plano, Texas USA 75074 **Tel** +1 469 241 9779 Toll Free 888 300 9779 Fax +1 469 241 0697

CipherLab Central Europe Willicher Damm 143-145 41066 Mönchengladbach Germany Tel +49 2161 56230 0 Fax +49 2161 56230 22