

# **U300-C** 3-inch Screen Fingerprint Time Attendance Terminal



### Introduction

The firmware of U300-C has been upgraded to the New Firmware. It brings many new experiences, including the new stunning GUI, rock-solid stability, faster matching speed and better expandability.

Users can easily manage data by networking U300-C via RS232/485, TCP/IP, and USB-host. Most importantly, all the functions can still operate in a networking state. U300-C is compatibility with various types of USB flash disks, ADMS and former SDK. It also supports data backup and retrieve to avoid the risk of accidental deletion.

It promotes the fingerprint time & attendance management to the next level. You can get the best of benefits from the U300-C.



### Features

#### Remarkable user experience

\* Intuitive and stunning UI designed with the most popular and internationalized element.

- \* Interface operation adopts modularized hierarchical design. Simpler, better and more logical.
- \* Faster matching speed: less than 0.5 second.

#### Enhanced features and performance

- \* User validity settings.
- \* Data backup and retrieve.
- \* Advanced User ID consisted of letters and numbers.
- \* Chip encryption for firmware protection.
- \* More flexible menu configuration: double line text display.
- \* Built-in Serial and Ethernet ports

#### Excellent expandability

\* Easy to extend functions and customize customers demand.



ขาย จำหน่าย บริการดิดตั้ง เครื่องพิมพ์ใบเสร็จ เครื่องอ่านบาร์โค้ด เครื่องพิมพ์บาร์โค้ด ระบบบาร์โค้ด อุปกรณ์บาร์โค้ด ระบบกล้องวงจรปิด ระบบสัญญาณกันขโมยบ้าน ไม้กั้นรถเข้า ออก

# Specifications

Fingerprint Capacity	3000
ID Card Capacity	10,000 (Optional)
Record Capacity	100,000
Display	3-inch Screen
Communication	RS232/485, TCP/IP,USB-host, USB-client
Standard Functions	SMS, Workcode, DST, Scheduled-bell, Self-Service Query, Automatic
	Status Switch
Optional Functions	ID/Mifare/HID, 9 digit user ID, Webserver, Photo ID, ADMS
Software	ZKTime 5.0 (Free), ZKTime. Net
Power Supply	DC 5V 2A
Verification Speed	≤0.5 Sec.
Operating Temp.	0°C-45°C
Operating Humidity	20%-80%
Dimension	181.6*126*49mm (Length*Width*Thickness)
Net Weight	1.2 kg

### **Dimensions (mm)**



### Interface



## Package List

















U300-C

Back Plate S

Screws and Holders

#### Software CD (ZKTime 5.0)

### USB Cable

Power Adapter

#### RJ45to485 Conversion Cable



ขาย จำหน่าย บริการติดตั้ง เครื่องพิมพ์ใบเสร็จ เครื่องอ่านบาร์โค้ด เครื่องพิมพ์บาร์โค้ด ระบบบาร์โค้ด อุปกรณ์บาร์โค้ด ระบบกล้องวงจรปิด ระบบสัญญาณกันขโมยบ้าน ไม้กั้นรถเข้า ออก



# Configuration

