

TP809 3" Thermal Receipt Printer

- Fashionable design
- Top paper loading
- Front exit
- High printing speed up to 260mm/s
- 2"&3" printing paper widths available
- Versatile interfaces: USB, Serial, Ethernet, Bluetooth, Wi-Fi, Cashdrawer
- Provide Windows, Linux, POSReady, OPOS driver
- SDK for iOS, Android & Windows



Front Exit



Compact Design



Specification

Item	Parameter	
Printing	Print Method	Direct Thermal Line Printing
	Resolution	Standard 203dpi (8dots/mm), Emulated 180dpi(7dots/mm)
	Print Speed	Max.260mm/s
	Printing Width	80mm
Interface	Standard	USB+Serial+Ethernet
	Optional	Bluetooth or Wi-Fi
Page Mode	Support	
Memory	RAM	16 MB
	Flash	16 MB
Fonts	Chinese	GBK 24×24dots
	Alphanumeric	ASCII 9×17, 12×24dots
	User-defined	YES
	Codepage	45
Barcode	1D	UPC-A, UPC-E, EAN8, EAN13, CODE39, ITF, CODEBAR, CODE128, CODE93
	2D	PDF417, QR code
Graphics	Support bitmap printing with different density and user defined bitmap printing. (Max size of each bitmap is 64K, the total size of bitmap is 256k)	
Detection	Standard	Paper out sensor, cover open sensor
	Optional	Paper near end sensor
Reliability	TPH life	150km
	Cutter life	2 million cuts

Power Supply	Input	AC 100V-240V
	Output	DC 24V/2.5A
Paper	Paper Type	Thermal Receipt Paper
	Paper Width	58mm/80mm
	Paper Thickness	0.056~0.1mm
	Roll Paper Diameter	Max. OD ϕ83mm
	Paper Load	Easy paper loading
	Paper Cut	Partial cut or full cut
Environment	Operation	0°C~45°C, 25%~85%RH
	Storage	-30°C~60°C, 5%~95%RH
Physical	Dimension	165(L)x130(W)x119(H)mm
	Characteristics Weight	1.35KG (Without paper roll)
Options & Accessories		
USB/Serial Cable, Paper Roll, Power Adapter, Power Cord, CD, Quick Start Guide		
Software	Emulation	ESC/POS
	Driver	Windows2000/ XP / Win7/Win8 / Win10/POSReady/Linux/OPOS/ JavaPOS
	SDK	WinCE, Win Mobile, Android, iOS

